CS-8030 Specifications

BASIC SPECIFICATIONS:

Enterprise/Workgroup Multifunctional with optional Print and Scan Configuration: Standard 200 Sheet Dual Scan Document Processor, Duplex, 1,500 x 2 Systems. Sheet Letter Size Paper Decks, 525 x 2 Paper Drawers Plus 100 Sheet Multi-Purpose Tray. Optional Advanced Finishing and Paper Handling. Resolution: 600 DPI. Interpolated 1800 x 600 DPI Resolution / 256 Levels Fast 1200 Mode Print Resolution Standard 128MB RAM, 40GB Hard Disk Drive Copier Memory: Magnification: Full Size, 7 Reduction, 4 Enlargement Preset Ratios, Plus 25-400% Zoom 120V, 60Hz, 16A **Electrical Requirements:** 26.8"W x 30.9"D x 46.9"H Dimensions: Weight: 415 lbs 500,000 Pages Per Month Max Monthly Volume:

OUTPUT SPEEDS:

Warm-Up Time: Within 30 Seconds, Program and Scan During Warmup, Auto Start
First Copy Out: 2.9 Seconds (Faceup)
First Print Out: 2.5 Seconds (Facedown)
Pages Per Minute: 80 Letter, 50 Legal, 40 Ledger

PAPER SUPPLY:

Standard Paper Sources:

1,500 x 2 Sheet Letter Size Paper Decks, Dual 525 Sheet Universal Paper Drawers, 100 Sheet MPT, Auto Selection / Switching, Add Paper While Running

Drawer Paper Size:

5.5" x 8.5" - 11" x 17"

MPT Paper Size:

5.5" x 8.5" - 11" x 17"

Std / Max Paper Capacity:

4,150 / 8,150

Paper Weight:

16 lb Bond - 90 lb Index via Paper Drawers,
13 lb Bond - 110 lb Index via MPT

Input Materials:

Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

DOCUMENT PROCESSOR:

Type: Dual Scan Document Processor (DSDP)

Acceptable Originals: 5.5" x 8.5" – 11" x 17", Mixed Size Processing

Capacity: 200 Sheet DSDP / 80 Letter Size Originals Per Minute

Paper Weight: 13 - 43 lb Bond

DUPLEX UNIT:

 Paper Size:
 5.5" x 8.5" - 11" x 17"

 Paper Weight:
 16 - 28 lb Bond

 Duplex Modes:
 Standard 1:2, 2:2, Book: 2, 2:1

COPY FUNCTIONS:

Imaging Modes: Text, Photo, Text / Photo, Auto, Manual, ECO
Continuous Copy: Up to 9,999, Auto Reset to 1
Additional Features: Auto Center, Magnification and Paper Select, Batch Copy, Booklet Mode, Book Mode, Combine Image, Covers, Inserts, Erase Mode, Image Overlay, Image Rotate, Image Reverse, Interrupt, Job Build, 9 Job Reserves, Job Queue, Margin Shift, Mirror Image, Memo Mode, Modify Copy, Proof Copy, Page Numbering, Transparency Mode, Job Time Information, 1,000 Management Codes, XY Zoom, 3 Shortcut Keys
Document Management: Store Documents, File Merge, Forms
Composition, Repeat Copy

PAPER HANDLING OPTIONS:

PAPER DECK: PF-650

 Paper Capacity:
 4,000 Sheets

 Paper Weight:
 17 lb Bond - 90 lb Index

 Paper Size:
 8.5" x 11"

 Dimensions / Weight:
 14.6"W x 23.2"D x 27.3"H / 90.4 lbs

PAPER DECK: PF-660

 Paper Capacity:
 4,000 Sheets

 Paper Weight:
 17 lb Bond - 110 lb Index

 Paper Size:
 8.5" x 11", 8.5" x 14", 11" x 7"

 Dimensions / Weight:
 26.4"W x 22.8"D x 27.7"H / 99.2 lbs

MULTI-FUNCTIONAL FINISHER: DF-650

 Stack Capacity:
 Main Tray: 3,000 Sheets; Sub Tray: 200 Sheets

 Paper Size:
 Main: 8.5" x 11" - 11" x 17"; Sub: 5.5" x 8.5" - 11" x 17"

 Paper Weight:
 12 lb Bond - 110 lb Index

 Staple Capacity:
 50 Sheets: 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"

 Edge Staple Position:
 4 Positions: Top Left, Bottom Left, Left Side, Genter

 Saddle Stitch:
 8.5" x 11" - 11" x 17"; Up to 16 Sheets

 Dimensions / Weight:
 31.4"W x 25.2"D x 43.3"H / 161 lbs

MULTI TRAY: MT-1

Number of Trays:	5	
Capacity:	150 Sheets (8.5" x 11") Per Tray	
Paper Size:	5.5" x 8.5" — 11" x 17"	
Paper Weight:	12 lb Bond – 90 lb Index	
Dimensions / Weight:	14.5"W x 15.5"D x 22.6"H / 33 lbs	

BOOKLET FOLDER: BF-1

PUNCH UNIT: PH-4

 Paper Size:
 8.5" x 11" – 11" x 17"

 Paper Weight:
 12 lb Bond – 110 lb Index

 Number of Holes:
 2 and 3

 Weight:
 7 lbs

CONNECTIVITY OPTIONS:

PRINT: PRINT SYSTEM (V)

PRINT: I HIMI OTOI	LIVI (V)
Controller:	Embedded PowerPC750 / 600 MHz Controller
Printer Memory:	Standard 64MB, Upgradeable to 576MB via 100 Pin DIMMS,
	Optional e-MPS Printer HDD, Standard CF Card Slot (Type 1)
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL3 (PS3), KCGL (HP-GL/2),
	Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL XL/5e, 136 Outline Fonts for KPDL3,
	1 Bitmap Font
Windows® OS Compatibility:	Windows® 95/98/Me/NT4.x/2000/XP/2003
Novell® OS Compatibility:	Novell NetWare® 3.x/4.x/5.x/6.x
Mac OS Compatibility:	0S 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100BaseTX, High Speed USB 2.0, Parallel IEEE1284
KUIO LV Expansion Slots (2):	Optional e-MPS Hard Disk Drive
	Optional IB-23 Secure NIC
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX,
	Certified Uni Driver, Windows® 64-bit Drivers
Utilities:	KM-NET Viewer, PDF Direct Print, KX Spool Center, KM-NET for Clients,
	KM-NET Printer Disk Manager, Network Advanced Setup Utilities,
	PRESCRIBE Utilities

E-MPS HARD DISK DRIVE: HD-10

Enables e-MPS Functions: Private Print, Job Storage, Quick Copy, Proof and Hold, Virtual MailBoxes

NETWORK SCANNING: SCAN SYSTEM (G)

Resolution:	200, 300, 400, 600 DPI
Scan Speed:	Up to 80 Sheets Per Minute
File Formats:	PDF,TIFF
Connectivity:	Standard 10/100BaseTX
Supported Protocols:	TCP/IP
Scanning Features:	KM Document Flow System - Document Management System, Scan to PC/File, Scan to Mac, Scan to E-Mail, Scan to FTP,TWAIN
Driver:	TWAIN Driver, TWAIN Driver for Mac
Utilities:	KM DB-Assistant, KM Scanner File Utility, Scan to Mac Utility, KM Scanner Address Book, Address Book Editor, LDAP Converter Utility, Network Advanced Setup Utilities

KYOCAPTURE: DOCUMENT CAPTURE WORKFLOW SOLUTION

KYOcapture is a server based document capture application that provides an automated rules based worekflow at the MFP's operation panel

DATA SECURITY KIT: DATA SECURITY KIT (B)

Provides security overwrite for automatic and manual deletion of copy and print data

ADDITIONAL OPTIONS:

32/64/128/256MB DIMMs for Print System

Common Criteria Validated EAL3

Data Security Kit (B) Software V1.10E

'This validation for information security that this product earned i

* This validation for information security that this product earned ind\(\)cates that it conforms with security assurance requirements as a result of evaluations based on specific evaluation criteria and evaluation standard











Specifications and design are subject to change without notice.