

KM-F650+ Specifications

BASIC SPECIFICATIONS:

Configuration:	Desktop Fax with 33.6Kbps Modem and 250 Sheet Cassette, plus Standard Copying, Printing and Scanning Functions		
Compatibility:	ITU-T Group 3		
Scanning Resolution:	Standard:	203 dpi x 96 lpi	
	Fine:	203 dpi x 196 lpi	
	Super Fine:	203 dpi x 391 lpi	
		406 dpi x 392 lpi (interpolated)	
Print Resolution	Fax/Copy:	406 dpi x 391 lpi	
	Print:	600 dpi x 600 dpi	
Fax Memory:	Standard 8MB		
Memory Capacity:	Standard 480 pages		
Document Memory Backup:	Standard Flash Memory		
Coding System:	MH/MR/MMR		
Scanning Method:	CCD		
Print Method:	Laser		
Max Print Width:	8.2"		
Electrical Requirements:	108 - 132V, 47 - 63Hz		
Dimensions:	14.6"W x 18.5"D x 9.9"H		
Weight:	19.8 lbs		

SPEEDS:

Modem Speed:	33.6Kbps - 2.4Kbps with Automatic Fallback		
Transmission Speed:	3 spp Super G3		
Pages Per Minute:	6.5 Letter Copy & Print		

PAPER SUPPLY:

Standard Paper Sources:	250 Sheet Drawer		
Drawer Paper Size:	8.5" x 11"/8.5" x 14"		
Std/Max Paper Capacity:	250/500		
Paper Weight:	16-20 lb Bond		

DOCUMENT PROCESSOR:

Type:	ADF		
Acceptable Originals:	5.8" x 5" - 10.1" x 78.77"		
Capacity:	50 Sheet		
Paper Weight:	12 - 24 lb Bond		
Effective Scanning Width:	8.3"		
Quick Scan:	2.8 spp		

FAX FUNCTION:

DIALING CAPABILITIES:

One-Touch Dialing Keys:	28		
Program/One-Touch Keys:	4		
Speed-dialing Codes:	100		
Max. Numbers Stored:	132		
Redial Attempts/Intervals:	Up to 5/1 to 15 minutes		
Group Dialing:	4 Groups/131 numbers		
Other Dialing:	Chain Dialing, Directory Search Dialing, Pulse/Tone Dialing		
Max. Dialing Digits:	36		

ADDITIONAL FEATURES:

Transmission/Reception: Multi Access, Memory Transmission, Quick Memory Transmission, Delayed Transmission (10 timers), ECM, Auto Fax/Tel. Switch, Polling (144 Locations), Memory polling, Continuous Polling, Verification Stamp, Broadcast Transmission (144 locations), Distinctive Ring Detection (DRD), Memory Reception, Delayed Polling, Delayed Multi-Station Polling (10 timers/144 locations), Substitute Reception, Auto Reduction

Security Communication/Codes: Confidential Transmission/Reception (10 mailboxes), Password Communication, Access Codes

Journals and Lists: Transaction Journal, Communication Journal, One Touch List, Abbreviated Number List, Program List

UTILITIES:

Configuration Editor and Phonebook editor

PRINT:

Std/Max Memory:	5MB/5MB DRAM	
Windows™ OS Compatibility:	Windows 98/Me/NT4.x/2000/XP	
Connectivity :	Standard Parallel IEEE 1284	
Driver:	Windows GDI	
Utilities:	Status Monitor	

SCAN:

Resolution:	400 x 400 dpi	
File Format:	PDF, TIFF, JPEG, Bitmap	
Connectivity:	Standard Parallel IEEE 1284	
Scanning Type:	PC Scanning	
Driver:	TWAIN	
Utilities:	Standard Document Management Software	

COPIY:

Continuous Copy:	Up to 99	
Zoom:	70% to 100%	

PAPER HANDLING OPTIONS:

PAPER DRAWER:PF-40

Paper Capacity:	250 Sheets	
Paper Weight:	16 - 24 lb Bond	
Paper Size:	8.5" x 11", 8.5" x 14", A4	
Dimensions/Weight:	13.7"W x 16.9"D x 3.2"H/5.5 lbs	

ADDITIONAL OPTIONS:

Telephone Handset (HS-40)

CONSUMABLES

TK-40	All-in-One Cartridge	9,000 pages@3% Coverage*
	*based on ITU-T No. 1 chart in standard mode	
	Ships with one TK-40 All-in-One Cartridge	